

Ninja e-1 Main Specifications

| | | |
|--------------------------------------|---|---|
| Product name | Ninja e-1 | |
| Model | NX011ARF | |
| Length × width × height | 1,980 mm × 685 mm × 1,105 mm | |
| Wheelbase | 1,370 mm | |
| Min. ground clearance | 160 mm | |
| Seat height | 785 mm | |
| Caster/trail | 24.4° / 93 mm | |
| Motor | Interior permanent magnet synchronous motor | |
| Batteries | Lithium-ion battery pack x2 | |
| Voltage / Capacity | 50.4 V / 30 Ah ×2 | |
| Charging time | 3.7 hours x 2 | |
| Frame | Trellis (high-tensile steel) | |
| Suspension system | Front | Telescopic |
| | Rear | Bottom-Link Uni Trak, gas-charged shock with adjustable |
| Tire size | Front | 100/80-17M/C (52S) |
| | Rear | 130/70-17M/C (62S) |
| Brake system | Front | Single ø290 mm disc (Effective diameter: ø263 mm) |
| | Rear | Single ø220 mm disc (Effective diameter: ø193 mm) |
| Steering angle (left/right) | 35° / 35° | |
| Vehicle weight (including batteries) | 140 kg | |

*Kawasaki Motors, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colors may vary by market.

Z e-1 Main Specifications

| | | |
|--------------------------------------|---|---|
| Product name | Z e-1 | |
| Model | NR011ARF | |
| Length × width × height | 1,980 mm × 730 mm × 1,035 mm | |
| Wheelbase | 1,370 mm | |
| Min. ground clearance | 170 mm | |
| Seat height | 785 mm | |
| Caster/trail | 24.4° / 93 mm | |
| Motor | Interior permanent magnet synchronous motor | |
| Batteries | Lithium-ion battery pack x2 | |
| Voltage / Capacity | 50.4 V / 30 Ah ×2 | |
| Charging time | 3.7 hours x 2 | |
| Frame | Trellis (high-tensile steel) | |
| Suspension system | Front | Telescopic |
| | Rear | Bottom-Link Uni Trak, gas-charged shock with adjustable |
| Tire size | Front | 100/80-17M/C (52S) |
| | Rear | 130/70-17M/C (62S) |
| Brake system | Front | Single ø290 mm disc (Effective diameter: ø263 mm) |
| | Rear | Single ø220 mm disc (Effective diameter: ø193 mm) |
| Steering angle (left/right) | 35° / 35° | |
| Vehicle weight (including batteries) | 135 kg | |

*Kawasaki Motors, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colors may vary by market.