Z900, Z900 SE Specifications

Model Name		Z900 / Z900 SE
Overall Length x Width x Height		Z900: 2,065mm×830mm×1,075mm
		Z900 SE: 2,065mm×830mm×1,135mm
Wheelbase		1,450 mm
Road clearance		145 mm
Seat height		830 mm
Caster (Rake angle) / Trail		24.7° / 110 mm
Engine type		Liquid-cooled, 4-stroke In-Line Four, DOHC 16 valves
Displacement		948cm <sup>3</sup>
Bore x Stroke		73.4×56.0mm
Compression ratio		11.8:1
Starting system		Electric
Ignition system		Digital
Lubrication system		Wet sump
Engine oil capacity		4.0L
Fuel supply		Fuel injection
Transmission		6-speed, return
Clutch type (primary)		Wet multi-disc, manual
	1st	2.600 (39/15)
	2nd	1.950 (39/20)
Gear ratios	3rd	1.600 (24/15)
	4th	1.389 (25/18)
	5th	1.217 (28/13)
	6th	1.069 (31/29)
Primary/Secondary reduction		1.627 (83/51) / 2.933 (44/15)
Frame type		Trellis, high-tensile steel
Suspension	Z900	
	Front: ø41 inverted fork with rebound damping and spring preload	
	adjustment	
	Rear: Horizontal Back-link, gas-charged shock with rebound damping	
	and spring preload adjustability	
	Z900 SE	
	Front: Ø41 inverted fork with compression and rebound damping and	
	spring preload adjustment	
	Rear: Horizontal Back-link, Öhlins S46 gas-charged shock with	
	rebound	
	rebour	iu

Tires	Front	120/70ZR17M/C (58W)
	Rear	180/55ZR17M/C (73W)
Brakes	Front	Dual semi-floating ø300 mm discs
	Rear	Single ø250 mm disc
Steering angle (left/right)		33° / 33°
Curb mass		Z900: 213kg
		Z900 SE: 214kg
Fuel tank capacity		17L

 $<sup>{}^{*}</sup>$ The figures reflect overseas (non-Japanese) specifications.

 $<sup>{}^{*}\</sup>mathsf{Specifications}$  are subject to change without notice due to revisions.