

■ NAV 4e, NAV 4e LE, and NAV 4e LIMITED Specifications

Model Name	NAV 4e / NAV 4e LE / NAV 4e LIMITED	
Marketing Code	KNT009ASF / KNT009ESF / KNT009DSF	
Overall Length x Width x Height	NAV 4e : 2,910mm×1,310mm×1,960mm NAV 4e LE : 2,910mm×1,310mm×1,970mm NAV 4e LIMITED : 3,035mm×1,310mm×1,970mm	
Wheelbase	2,030mm	
Road clearance	185mm	
Motor type	Air-cooled induction motor	
Rated power	4.0 kW (Max power: 10.7 kW)	
Traction battery	NAV 4e: Lead-acid x 6/ 8 V NAV 4e LE / NAV 4e LIMITED: Lithium-ion battery x 2 / 51.7V	
Gear ratio	16.990	
Secondary reduction	Front	3.589 (25/24×20/19×36/11)
	Rear	3.538 (46/13)
Frame type	Ladder type, tubular steel	
Suspension type	Front	MacPherson strut
	Rear	Leaf springs with hydraulic shock absorbers
Tire size	Front	23 x 10.00-14
	Rear	23 x 10.00-14
Brakes	Rear	Drum (ø160 mm)
	Parking	Drum (ø160 mm)
Max. permissible load	363kg	
Curb mass	NAV 4e: 590kg / NAV 4e LE: 456kg / NAV 4e LIMITED: 476kg	

*The figures are based on non-Japan specifications.

*Specifications are subject to change without notice due to revisions.