

TERYX4 H2, TERYX4 H2 DELUXE, TERYX5 H2 DELUXE Specifications

Length x Width x Height		TERYX4 H2: 4,050 mm × 1,880 mm × 1,815 mm TERYX4 H2 DELUXE / TERYX5 H2 DELUXE: 4,050 mm × 1,880 mm × 1,875 mm (not including antenna)
Wheelbase		3,200 mm
Road clearance		410 mm (Max preload: 420 mm)
Seat height	Front	810 mm
	Rear	TERYX4 H2 / TERYX4 H2 DELUXE: 825 mm TERYX5 H2 DELUXE: 820 mm (left/right seats), 850 mm (center seat)
Caster (rake angle)		8.0°
Engine type/Valve system		Liquid-cooled, 4-stroke In-Line Four / DOHC, 4 valves per cylinder
Displacement		999 cm ³
Bore x Stroke		73.4 × 59.0 mm
Compression ratio		7.8:1
Intake system		Kawasaki Supercharger
Starting system		Electric
Ignition system		Digital
Lubrication type		Wet sump
Engine oil capacity		4.4 L
Fuel supply		Fuel injection
Transmission		Dual range (high/low) CVT with reverse
Gear ratios	Forward (High)	2.987 (41/40 × 36/20 × 34/21)
	Forward (Low)	6.165 (55/26 × 36/20 × 34/21)
	Reverse	4.463 (32/20 × 36/20 × 34/21)
Primary reduction ratio		3.479~0.795
Final reduction ratio	Front	3.589 (25/24 × 20/19 × 36/11)
	Rear	3.538 (46/13)
Frame type		Ladder type, tubular steel
Suspension	Front	Double wishbone
	Rear	4-Link Trailing Arm
Tire size	Front	33 × 10.00R16
	Rear	33 × 10.00R16
Brakes	Front	Hydraulic discs 270 mm (External diameter)
	Rear	Hydraulic discs 270 mm (External diameter)
Max. permissible load		488 kg
Curb mass		TERYX4 H2: 1,100 kg TERYX4 H2 DELUXE: 1,132 kg TERYX5 H2 DELUXE: 1,137 kg
Estimated dry mass		TERYX4 H2: 1,039 kg TERYX4 H2 DELUXE: 1,071 kg TERYX5 H2 DELUXE: 1,076 kg
Fuel tank capacity		49 L

* The figures reflect overseas (non-Japanese) specifications.

* Specifications and dimensions are subject to change without notice due to revisions.